



CERTIFICATE OF CONFORMITY

This is to certify that

**DuPont™
Tyvek® HomeWrap**

Breathable, Fire Retardant, Synthetic Wall Underlay



Product Description

DuPont™ Tyvek® HomeWrap is a breathable wall wrap designed to, allow moisture vapour to pass through whilst preventing transfer of liquid water. This helps promote drying in wall systems, to help prevent mould and water damage. Tyvek® HomeWrap stops air movement through the walls, helping insulation perform closer to its full R-value, to provide a more energy-efficient home

Product Purpose or Use

This product is certified for use as a wall underlay.

Certificate Holder

DuPont™ Australia Ltd

ABN: 59 000 716 469
Level 3,7 Eden Park Drive
Macquarie Park NSW
Australia 2113
Ph: 02 9923 6148
W: www.dupont.com.au



Certification Body

CertMark International Pty Ltd

T/A CertMark New Zealand
ABN: 80 111 217 568
JAS-ANZ Accreditation No. Z4450210AK
PO Box 321 Tuakau 2121
www.CertMark.org

Complies with the New Zealand Building Code:

1. B2 Durability: Performance B2.3.1 (a) & B2.3.2.
2. C3 Fire Affecting Areas Beyond the Fire Source C3.4(c)
3. E2 External Moisture: Performance E2.3.2.
4. F2 Hazardous Building Materials: Performance F2.3.1.

Subject to the following Conditions & Limitations:

- a. This certificate must be read in conjunction with the Schedule of Product Compliance below.
- b. Tyvek® HomeWrap must be installed as per DuPont™ Tyvek® Wall Underlay Install Guidelines April 2015—New Zealand.
- c. Underlay must fit tightly and be lap taped around penetrations, allowing for free drainage of condensation.
- d. Tyvek® HomeWrap is suitable for use with LOSP treated timber, conditional upon the solvent in LOSP treated timber having had sufficient time to evaporate (usually 4 days after treatment under appropriate environmental conditions).
- e. Tyvek® HomeWrap is non-directional and hence can be installed inside out or upside down without affecting performance.
- f. The product must be used behind claddings that meet the requirements of the NZBC, such as those covered by NZBC Acceptable Solution E2/AS1.
- g. This certification relates only to the product that is described herein, and has to be read, considered and used as a whole document — it may be considered misleading and will be incomplete to be selective.

John Thorpe
CertMark International Pty Ltd

27/07/2015
Date of Issue

27/07/2018
Review Date

CMA-CM40140
Certificate Number

- This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation & Employment (MBIE) under the Building Act 2004. MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms to the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the MBIE website, www.mbie.govt.nz
- This certificate may only be reproduced in its entirety.





Schedule of Product Compliance



B2 – Durability	Provided the product is used, designed, installed and maintained in accordance with DuPont™ Tyvek® Wall Underlay Install Guidelines April 2015—New Zealand the product will satisfy Performance Clause B2.3.1 (a), not less than 50 years and B2.3.2.
C3 – Fire Affecting Areas Beyond the Fire Source	Provided the product is used, designed, installed and maintained in accordance with DuPont™ Tyvek® Wall Underlay Install Guidelines April 2015—New Zealand the product will satisfy Performance Clause C3.4(c) where suspended flexible fabrics and membrane structures used in the construction of buildings must have properties resulting in a low probability of injury or illness to persons not in close proximity to a fire source.
Section D – Not applicable.	
E2- External Moisture	Provided the product is used, designed, installed and maintained in accordance with DuPont™ Tyvek® Wall Underlay Install Guidelines April 2015—New Zealand the product will satisfy Performance Clause: E2.3.2.
F2- Hazardous Building Materials	Provided the product is used, designed, installed and maintained in accordance with DuPont™ Tyvek® Wall Underlay Install Guidelines April 2015—New Zealand the product will satisfy Performance Clause: F2.3.1. DuPont Tyvek® HomeWrap meets this requirement and will not present a health hazard to people
Section G – Not applicable.	
Section H – Not applicable.	

End of Schedule

- This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation & Employment (MBIE) under the Building Act 2004. MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms to the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the MBIE website, www.mbie.govt.nz
- This certificate may only be reproduced in its entirety.

