



CODEMARK™

Product description

The Asphalttech Tanking System is based on a hot-applied membrane based on polymer modified mastic asphalt and associated components. The membrane is applied in two layers to provide a waterproofing layer with a nominal thickness of 6mm.

System Components:

Shieldflex PR	Shield CP
Shield CP Super	PermaTEC EcoWrap
PermaFLASH-R	PermaFLASH-D150
PermaFLASH-500	PermaGUARD-F
PermaGUARD-M	PermaGUARD-HDPB,
PermaGUARD-PB	IKO PermaTEC,
IKO PermaTEC Polymer Primer	

Product purpose or use

This product certificate covers the use of the Asphalttech Tanking System to resist the passage of ground water and water vapor to the inside of the building.

Certificate holder

Asphalttech Waterproofing Products Ltd
28b Parkway Drive, Mairangi Bay, Auckland,
Ph: 09 475 9725
Email: admin@asphalttech.co.nz
Web: www.asphalttech.co.nz

CodeMark Product Certification Body

Bureau Veritas Australia Pty Ltd
3/435 Williamstown Road,
Port Melbourne VIC, 3207 Australia
Ph: 1800 855 190
product.certification@au.bureauveritas.com
www.bureauveritas.com.au

Sam Guindi
Product Certification Manager

For and on behalf of
Bureau Veritas Australia Pty Ltd

PRODUCT CERTIFICATE

This is to certify that

Asphalttech Tanking System



**BUREAU
VERITAS**

Complies with the New Zealand Building Code (NZBC):

If designed, used, installed and maintained in accordance with the scope of this certificate, the above mentioned product will meet the following provisions of the NZBC:

- B1 Structure – B1.3.1, B1.3.3 (e), B1.3.4
- B2 Durability – B2.3.1 (a), B2.3.2 (a)
- E2 External Moisture – E2.3.3, E2.3.7
- F2 Hazardous Building Materials – F2.3.1

Subject to the following conditions and limitations:

1. The Asphalttech Tanking System must be installed in accordance with the relevant requirements of CP 105:1973, Section 2, BS 8102:1990 and the Asphalttech Mastic Asphalt Technical Manual 002.
2. The substrate must be dry, with no sharp projections.
3. All work must be carried out by Asphalttech Waterproofing Products Ltd approved applicators.
4. Reasonable care in construction is required to avoid prolonged loading by sharp objects.



WWW.JAS-ANZ.ORG/REGISTER

19 March 2019
Date of issue

CM70011
Certificate Number



**MINISTRY OF BUSINESS,
INNOVATION & EMPLOYMENT**
HĪKINA WHAKATUTUKI

- This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.
- The certificate holder must maintain compliance with the conditions set out in section 15 of the Building (Product Certification) Regulations 2008. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.