



CODEMARK™

Product description

DriStud RU 24 is a non-fire retardant, black faced synthetic tri-laminate roofing underlay that is water resistant and vapour permeable. It is a heavy grammage Vapour Permeable Synthetic Self Support Roof Underlay (Non Fire Retardant). The underlay is branded with the DriStud RU24 Self Supporting Roof Underlay branding.

Product purpose or use

DriStud RU 24 is a roofing underlay intended for use on all new and existing buildings in wind zones up to and including 'Extra High', as defined in NZS 3604:2011 Timber-framed buildings. DriStud RU 24 can be used where both heavy weight and/or self-support roof underlay is specified.

Certificate holder

TCL Hunt Ltd
7 Fisher Cres, Mt Wellington, Auckland 1064
PO Box 132-166, Sylvia Park, Auckland, 1644
www.dristud.co.nz
Ph +64 9 526 2700

CodeMark Product Certification Body

Bureau Veritas Australia Pty Ltd
3/435 Williamstown Road,
Port Melbourne VIC, 3207
Ph: 1800 855 190
www.bureauveritas.com.au

Sam Guindi
Product Certification Manager

For and on behalf of
Bureau Veritas Australia Pty Ltd

PRODUCT CERTIFICATE

This is to certify that

DriStud RU 24 Roof Underlay

Complies with the New Zealand Building Code (NZBC):

If designed, used, installed and maintained in accordance with the scope of this certificate, the above mentioned product will meet or contribute to meeting the following provisions of the NZBC:

- Durability** B2.3.1 (b), B2.3.2 (a)
- External Moisture** E2.3.2, E2.3.7
- Hazardous Building Materials** F2.3.1

Subject to the following conditions and limitations:

1. Must be installed in accordance with the DriStud RU 24 Installation Guide Rev 3.0 (March 2019). This is available at www.dristud.co.nz
2. DriStud RU 24 may be installed over both timber and steel roof framing.
3. This certificate covers the use of DriStud RU 24 under: Masonry Tiles, Terracotta tiles, Metal tiles, Profiled metal claddings, slate and composite panels.
4. DriStud RU 24 can span up to 1200mm between adjacent supports. Where the span exceeds 1200mm or the roof pitch is $\leq 10^\circ$ a corrosion resistant mesh or alternative i.e. plastic strapping must be used.



**BUREAU
VERITAS**



WWW.JAS-ANZ.ORG/REGISTER

31 October 2019
Date of issue

CM70020
Certificate Number



**MINISTRY OF BUSINESS,
INNOVATION & EMPLOYMENT**
HĪKINA WHAKATUTUKI

- This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificates conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.
- The certificate holder must maintain compliance with the conditions set out in section 15 of the Building (Product Certification) Regulations 2008. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.