



CERTIFICATE OF CONFORMITY

This is to certify that
DuPont™
FlexWrap™ NF



Product Description

DuPont™ FlexWrap™ NF is a stretchable & flexible wrap made up of 3 components:

1. DuPont™ Tyvek® top sheet providing a water tight layer.
2. 100% Butyl Rubber as an adhesive layer
3. A paper release liner.

Product Purpose or Use

To be used to create a watertight adhesion to all Tyvek® breather membranes around non-straight penetrations & corners of all rough openings such as: dormers, window & door sills, chimney breasts, pipe penetrations and any custom shapes.

Certificate Holder

DuPont (Australia) Pty Ltd

ABN: 59 000 716 469

Level 3,7 Eden Park Drive
Macquarie Park NSW
Australia 2113

Ph: 02 9923 6148

W: www.dupont.com.au



Tyvek.

Certification Body

CertMark International Pty Ltd

T/A CertMark New Zealand

ABN: 80 111 217 568

JAS-ANZ Accreditation No. Z4450210AK

PO Box 321 Tuakau 2121

+64 (09) 951 8246

www.CertMark.org

Complies with the New Zealand Building Code:

1. B2.3.1 (b) and B2.3.2.
2. F2.3.1.

If designed, installed and maintained in accordance with the purpose, use, scope and conditions of this certificate, DuPont FlexWrap NF will assist compliance with:

3. E2.3.2.

Subject to the following Conditions & Limitations:

- a. The certificate holder must maintain compliance with the conditions set out in section 15 of the building (Product Certification) Regulations 2008.
- b. Ensure all surfaces to which DuPont™ FlexWrap™ NF is applied are free from dirt, moisture, ice, grease and other materials which could reduce the adhesion.
- c. DuPont™ FlexWrap™ NF is to be installed when dry and when the roll temperature is warmer than -4°C/25°F.
- d. When applying DuPont™ FlexWrap™ NF to LOSP (light organic solvent preservative) treated timber, ensure the solvent has been allowed to flash off prior to installing the product. It is suggested that a minimum of one (1) week is allowed for.
- e. DuPont™ FlexWrap™ NF when used, installed and maintained in accordance with the requirements outlined in DuPont™ DuPont Flashing Installation Guidelines April, 2015—New Zealand & Australia contributes to the requirements of Acceptable Solution E2/AS1 Amendment 6, Clause 9.1.5 (b) (i).
- f. After completion of the installation DuPont™ FlexWrap™ NF has to be covered within 30 days with the appropriate building cladding materials.


John Thorpe
CertMark International Pty Ltd

27/04/2015

Date of Issue

CMA-CM40141(Rev1)

Certificate Number

Revised February 2016

• This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation & Employment (MBIE) under the Building Act 2004. MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms to the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate

• It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the MBIE website, www.mbie.govt.nz

• This certificate may only be reproduced in its entirety.

