




PRODUCT CERTIFICATE

Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System



KEY INFORMATION

CERTIFICATE: GM-CM30037 Rev1

| | | | |
|---|---|---------------------------------|----------------------------|
| 1 SUMMARY OF DESCRIPTION OF BUILDING METHOD OR PRODUCT The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System is a cavity-based external wall cladding system for residential and light commercial type buildings where domestic construction techniques are used. | | | |
| 2 SUMMARY OF INTENDED USE OF BUILDING METHOD OR PRODUCT 1. The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System has been assessed as an external horizontally fixed wall cladding system for buildings within the following scope: <ul style="list-style-type: none"> the scope limitations of NZBC Acceptable Solution E2/AS1, Third Edition including amendment 9 (27/06/2019), Paragraph 1.1; and, constructed with timber framing complying with the NZBC and, with a risk score of 0-20, calculated in accordance with NZBC Acceptable Solution E2/AS1, Third Edition including amendment 9 (27/06/2019), Table 2; and, situated in NZS 3604:2011 Wind Zones up to, and including Extra High. 2. The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System has also been assessed for weathertightness and structural wind loading when used as an external horizontally fixed wall cladding system for buildings within the following scope: <ul style="list-style-type: none"> the scope limitations of NZBC Acceptable Solution E2/AS1, Third Edition including amendment 9 (27/06/2019), Paragraph 1.1; with regards to building height and floor plan area; and, constructed with timber framing subject to specific engineering design; and, situated in specific design wind pressures up to a maximum design differential ultimate limit state (ULS) of 2.5 kPa. 3. The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System must only be installed horizontally on vertical, flat, surfaces. 4. The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System is assessed for use with aluminium window and door joinery that is installed with vertical jambs and horizontal heads and sills. (The assessment of the Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System relies on the joinery meeting the requirements of NZS 4211:2008 including Amendment 1 for the relevant Wind Zone or wind pressure.) | | | |
| 4 CERTIFICATE HOLDER DETAILS Herman Pacific Limited. Herman Pacific 110 Foundry Road, Silverdale 0932, New Zealand. technical@hermpac.co.nz Tel: 09 426 5475, Fax: 09 426 7638, www.hermpac.co.nz | ISSUED 31/3/2014 | LAST UPDATE 23/8/2020 | EXPIRY 31/3/2023 |
| | 5 SIGNATURE  Herve Michoux, Global Mark Managing Director | | |
| 6 PRODUCT CERTIFICATION BODY Global-Mark Pty Ltd 57 Willis Street Wellington, 6011 customer.service@global-mark.co.nz +64 9 889 0622 www.global-mark.co.nz The complaints process for this certificate can be found here: https://www.global-mark.com.au/?s=complaint | | | |



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004.

This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

CERTIFICATE V1.2

PRODUCT CERTIFICATE

Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System

3 BUILDING CODE PROVISIONS

The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System if designed, used, installed and maintained in accordance with the scope of this Certificate, the statements and conditions of the supporting BRANZ Appraisal No. 658 (2020), the Hermpac Rusticated, Splaycut & Multi-Splay Weatherboard Cavity System Installation Specification, May 2020 will meet the following provisions of the NZBC:

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2, B1.3.4 (b), (c), (d) and (e) for the relevant physical conditions of B1.3.3 (a), (h), (j) and (q). The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System meets the requirements.

Clause B2 DURABILITY: Performance B2.3.1(b) 15 years and B2.3.2(a). The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System meets these requirements.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2. The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System meets this requirement.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. The Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System meets this requirement and will not present a health hazard to people.

7 CONDITIONS AND LIMITATIONS OF USE

1. Subject to regular inspection for soil movement, earthquake or other structural impact or user damage.
2. Maintaining the validity of BRANZ Appraisal No. 658 (2020) Hermpac Rusticated, Splaycut and Multi-splay Weatherboard Cavity System.
3. Proprietary stain systems and proprietary paint systems have not been evaluated, and are therefore outside the scope of this certification.
Design Conditions:
4. Product specification and incorporation of the Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System into the building design shall be carried out by a designer / architect / engineer or a building professional who:
 - a. Is qualified to design the buildings covered under the 'Scope' of use of this product.
 - b. Has ready access to the technical specifications including construction drawings and standards referenced in both the BRANZ appraisal No. 658 (2020) Hermpac Rusticated, Splaycut and Multi-splay Weatherboard Cavity System and this certificate.Product Installation Conditions:
5. Installation shall be carried out by a Licensed Building Practitioner (LBP), or tradespersons with experience in Rusticated, Splaycut and Multi-Splay Weatherboard external wall cladding installation who are supervised by a LBP.
6. Installation shall be undertaken in accordance with all relevant technical information related to the selected installation method, including information contained within the BRANZ appraisal No. 658 (2020), the Hermpac Rusticated, Splaycut & Multi-Splay Weatherboard Cavity System Installation Specification, May 2020, including
 - a. the construction drawings applicable (see section 9)
 - b. The finish requirements applicable to species and the stain or paint system used.
7. As part of the application for the Code Compliance Certificate (CCC), a signed Quality Assurance Checklist Hermpac Rusticated, Multi-Splay & Splaycut Weatherboard Cavity System (dated May 2020) must be supplied by the LBP who installed or supervised installation.

8 HEALTH AND SAFETY INFORMATION



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004.

This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>. The purpose of construction site audits is to confirm the practicability of installing the product; and to confirm the appropriateness and accuracy of installation instructions. In issuing this certificate, Global-Mark has relied on the independent expert and/or laboratory advise or reports. In placing the CodeMark mark on the product/system, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein.

PRODUCT CERTIFICATE

Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System

Standard industry safety practices and manufacturer safety requirement as detailed in the technical literature including the applicable SDS must be observed at all time.

9 SUPPORTING INFORMATION ABOUT DESCRIPTION

1. The system consists of horizontally fixed Rusticated, Splaycut and Multi-Splay Weatherboards installed over battens to form the cavity, flashings and accessories.
2. The Hermpac Rusticated, Splaycut and Multi-Splay weatherboards are manufactured from Western Red Cedar. Selected Weatherboards are also manufactured from DuraLarch and AshinDura. Cedar and DuraLarch weatherboards are supplied either raw, with one coat of machine applied premium penetrating exterior grade oil stain to Hermpac specifications or, with a machine applied primer coat and one machine applied undercoat of exterior grade paint to Hermpac specifications. AshinDura weatherboards are treated to H3.1 and are only available with a machine applied primer coat and one machine applied coat of exterior grade paint to Hermpac specifications.
3. The system incorporates a primary and secondary means of weather resistance (first and second line of defense) against water penetration by separating the cladding from the external wall frame with a minimal 18 mm drained cavity.
4. Hermpac Standard Profiles (HP51, HP52, HP65, HP65MS, HP66, HP66MS, HP67, HP68, HP53, HP54 and HP57) and Hermpac Custom Profiles defined in accordance with NZS3617 and BRANZ Bulletin 411 are covered by this certificate
5. The system construction details defined in:
 - Rusticated, Splaycut & Multi-Splay Weatherboard Cavity System – Construction Drawings -Version 1.2 dated 20 May 2020; and
 - Rusticated Random Width & Depth Weatherboard Cavity System – Construction Drawings -Version 1.2 dated 20 May 2020.

10 SUPPORTING INFORMATION ABOUT INTENDED USE

Nil

11 SUPPORTING INFORMATION ABOUT CONDITIONS AND LIMITATIONS OF USE

Nil

12 BASIS FOR CERTIFICATION

The certification decision is based independent technical review(s) of engineering opinion(s) and other documented evidence(s), factory audit(s) and site review(s)

13 SUPPORTING DOCUMENTATION FOR CERTIFICATION

| Ref | Author | Title | Date and/or revision |
|-----|----------------|--|----------------------|
| 1 | BRANZ | Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System - BRANZ Appraisal No. 658 (2020) | 27/05/2020 |
| 2 * | BRANZ | BRANZ Appraisals Means of Compliance - Basis of Appraisal - Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System - BRANZ Appraisal No. 658 (2020) | TV10664-004 |
| 3 | Herman Pacific | Hermpac Weatherboard Cladding Cavity Systems – SDS Index | 20-May-2020 |

* This document was provided commercial in confidence and is not publicly available.

14 CONDITIONS RELATING TO NOTIFICATION

- (a) the certificate holder notifies the product certification body in writing of any intended change to any of the following particulars:
- (i) the name, address, or contact details of the certificate holder;
 - (ii) any address of a location where a certified product is produced or manufactured;

PRODUCT CERTIFICATE

Hermpac Rusticated, Splaycut and Multi-Splay Weatherboard Cavity System

- (b) the certificate holder notifies the product certification body in writing of any intended change, modification, or alteration to any of the following:
- (i) the certified building method or product;
 - (ii) the method of its production or manufacture;
 - (iii) the product quality plan prepared in respect of the certified building method or product;
 - (iv) the application or installation instructions for the certified building method or product;
 - (v) any documentation relating to the use and maintenance of the certified building method or product;
- (c) if the certificate holder has any reason to suspect that the certified building method or product does not comply with the Building Code, the certificate holder notifies the product certification body in writing of the reason for that suspicion:
- (d) if the certificate holder or the product certification body finds that a certified building method or product that has been released on the market does not comply with the Building Code, the certificate holder discloses that fact in disclosure statements published in a form that is acceptable to the product certification body and to the chief executive:
- (e) if the certificate is suspended or revoked, the certificate holder—
- (i) notifies all customers to whom the building method or product is regularly supplied; and
 - (ii) immediately ceases using the certificate, the mark of conformity, and any reference to the number of the certificate.

End of document