

Certificate no: CMNZ10028

Version: 01

Original issue date: 27 March 2024

Version date: 27 March 2024

1. Certificate Holder Details



ITW New Zealand Ltd
t/a Pryda New Zealand
8 Orbit Drive
Albany
Auckland 0632
Tel: 0800 882 244
Email: info@prydaanz.com
Web: <http://www.pryda.co.nz>

2. Product Certification Body

BRANZ Limited
1222 Moonshine Road
RD1, Porirua 5381
Private Bag 50 908
Porirua 5240
Tel: 04 237 1170
Email: assuranceservices@branz.co.nz
Web: branz.nz

Complaints: The complaints process for this certificate can be found here:
<https://www.branz.co.nz/codemark-info/complaints-and-appeals/>
<https://www.branz.co.nz/codemark-info/complaints-and-appeals/>

Product Certificate

Pryda Connectors and Engineered Systems - Foundation Fixings

3. Description of Building Method or Product

Pryda Connectors and Engineered Systems - Foundation Fixings are a range of metal plate connectors manufactured from galvanised steel coil or sheet, or from stainless steel. For more product details, refer to Section 10.

This Product Certificate covers the following Foundation Fixings:

- NZ Pryda Stud Anchor
- NZ Pole to Girt Bracket
- NZ Pryda Sheet Brace Strap

4. Intended use of Building Method or Product

Pryda Connectors and Engineered Systems - Foundation Fixings are a range of structural connectors for the following uses:

- The NZ Pryda Stud Anchor is for fixing timber studs to timber bottom plates to prevent uplift with a capacity of 6 kN or 12 kN in accordance with NZS 3604.
- The NZ Pole to Girt Bracket is for fixing timber girts to a timber post or round timber pole with load capacities for different load cases as detailed in the Reference Documents for Specific Engineering Design use.
- The NZ Pryda Sheet Brace Straps are for use in timber framed walls and can be used to fix timber studs to timber bottom plates, timber lintels to timber studs and timber studs to timber floor framing to prevent uplift with a capacity of 7.5 kN in accordance with NZS 3604.

5. New Zealand Building Code Provisions

COMPLIES WITH THE FOLLOWING PROVISIONS OF THE NEW ZEALAND BUILDING CODE (NZBC)

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Loads arising from self-weight, imposed gravity loads arising from use, earthquake, snow, and wind. (i.e. B1.3.3 (a), (b), (f), (g), and (h)) (contributes).

Clause B2 DURABILITY: Performance B2.3.1 (a) not less than 50 years and B2.3.2.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10028

Version: 01

Original issue date: 27 March 2024

Version date: 27 March 2024

Product Certificate

Pryda Connectors and Engineered Systems - Foundation Fixings



6. Conditions and Limitations of Use

- Applications are limited to timber-framed structures designed in accordance with NZS 3604.
- Pryda Connectors and Engineered Systems – Foundation Fixings shall be:
 - Used for buildings within the limitations of NZS 3604; and,
 - Product material and corrosion resistance coating shall be as specified in NZS 3604. The fastener material shall match the material of the selected product; and,
 - Used in accordance with the limitations stated in the Reference Documents; and,
 - Installed in accordance with the installation instructions detailed in the Reference Documents, in particular, the number, specification and fixing pattern of the fasteners must be followed.
 - Used with minimum JD5 timber as defined in NZS AS 1720.1.
- The following product specific limitations shall apply:
 - NZ Pryda Stud Anchor has a design capacity of 6 kN when used as a single stud anchor and 12 kN when used in pairs.
 - NZ Pole to Girt Brackets shall be installed in pairs to the top and underside of the girt as defined in the Reference Materials.
 - NZ Pryda Sheet Brace Strap has a design capacity of 7.5 kN.

Reference Documents:

- Pryda Product Data Sheet, NZ Pryda Stud Anchor, December 2023, V1.02.
- Pryda Product Data Sheet, NZ Pole to Girt Bracket, December 2023 – V1.02.
- Pryda Product Data Sheet, NZ Pryda Sheet Brace Straps, December 2023 – V1.02.
- Pryda Product Data Sheet, NZ Pryda Connector Screws and Nail, December 2023 – V1.02.

7. Health and Safety Information

Pryda Connectors and Engineered Systems - Foundation Fixings are manufactured from galvanised steel or stainless steel. Manufacturer's instructions and typical practices for working with, handling and maintaining these materials should be observed.

8. Basis for Certification

The following evaluations have been carried out on Pryda Connectors and Engineered Systems - Foundation Fixings to determine compliance with the NZBC:

- Compliance with NZBC B1 Structure performance requirements was determined by a BRANZ SME through assessing test reports of the products against NZS 3604 requirements and claims made within the Reference Documents.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10028

Version: 01

Original issue date: 27 March 2024

Version date: 27 March 2024

Product Certificate

Pryda Connectors and Engineered Systems - Foundation Fixings



- Compliance with NZBC B2 Durability performance requirements was determined by a BRANZ SME through assessing the scope limitations of the individual components against the material requirements of NZS 3604.
- Compliance with NZBC F2 Hazardous Building Materials performance requirements was determined by a BRANZ SME through assessing the different grades of materials and their uses.
- The Reference Documents have been examined by BRANZ and found to be satisfactory.
- The quality of supply to market is the responsibility of ITW New Zealand Ltd (t/a Pryda New Zealand).
- Building designers are responsible for the design of the building, and for the incorporation of the Pryda Connectors and Engineered Systems - Foundation Fixings into their design in accordance with this Product Certificate and the Reference Documents.
- Quality of installation is the responsibility of the installer in accordance with the Reference Documents of ITW New Zealand Ltd (t/a Pryda New Zealand).

9. Supporting Documentation for Certification

- AS/NZS 3604:2011 Timber-framed buildings.
- Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B1 Structure, 1st Edition, Amendment 21, 2 November 2023.
- Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B2 Durability, 2nd Edition, Amendment 12, 28 November 2019.
- Acceptable Solutions and Verification Methods for New Zealand Building Code Clause F2 Hazardous Building Materials, 1st Edition, Amendment 3, 1 January 2017.
- BRANZ Ltd Structures Test Report TP17360-A-01, Pryda Connection Testing Group A, dated 23 February 2024.
- Ministry of Business, Innovation and Employment Record of amendments – Acceptable Solutions, Verifications Methods and handbooks.
- NZS AS 1720.1:2022 Timber Structures.
- The Building Regulations 1992.

10. Supporting Information About Description

Product Specification

- **NZ Pryda Stud Anchor** is available as a 6 kN or 12 kN stud tie-down and is manufactured from G300 Z275 steel with a BMT of 2 mm. The dimensions are 85 mm x 30 mm x 80 mm. It is fastened with NZ Pryda Timber Connector Nails or 12 g x 35 mm NZ Pryda Timber Connector Screws. The product code is SBA. The product is identified on the product packaging label by the product code and product name.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10028

Version: 01

Original issue date: 27 March 2024

Version date: 27 March 2024

Product Certificate

Pryda Connectors and Engineered Systems - Foundation Fixings



- **NZ Pole to Girt Brackets** are used to fix timber girts to a timber post or round timber pole and are manufactured from G300 Z275 steel or Grade 304 stainless steel with a BMT of 0.95 mm. They are fastened with NZ Pryda Timber Connector Nails and used in pairs. The dimensions are 50 x 50 x 110 mm. The product code is NPP2G for galvanised and NPP2G/S for stainless steel. The product is identified on the product packaging label by the product code and product name.
- **NZ Pryda Sheet Brace Straps** are tie-down fixings for wall panels and are manufactured from G300 Z275 steel or Grade 304 stainless steel with a BMT of 1 mm. They are 25 mm wide and available in the following lengths: 300 mm (product codes SB300 for galvanised and SB300/S for stainless); 400 mm (product codes SB400 for galvanised and SB400/S for stainless); 600 mm (product codes SB600 for galvanised and SB600/S for stainless); 10 m (galvanised only, product code SBS10M); and 30 m (galvanised only, product code SBS30M). They are fastened using NZ Pryda Timber Connector Nails. The product is identified on the product packaging label by the product code and product name.

Accessories supplied by Pryda:

- **NZ Pryda Timber Connector Nails** are 35 x 3.15 mm and are manufactured from galvanised steel or Grade 316 stainless steel. The product codes are OSNGB or OBSNBCI/SS. The product is identified on the product packaging label by the product code and product name.
- **NZ Pryda Connector Screws** are available in 12 g x 35 mm (product code TCS12-35) and 12 g x 65 mm (product code TCS12-65). They are zinc galvanised, Class 3. The product is identified on the product packaging label by the product code and product name.

11. Supporting Information About Intended Use

Installation Requirements

Installation must be carried out in accordance with the Reference Documents and NZS 3604.

Building Code

B1 STRUCTURE – Pryda Connectors and Engineered Systems - Foundation Fixings will resist structural loads likely to be encountered in normal use.

B2 DURABILITY – Pryda Connectors and Engineered Systems - Foundation Fixings, when installed in accordance with the details given in the Reference Documents and NZS 3604, meet code compliance with NZBC Clause B2.3.1 (a) not less than 50 years as a building element that provides structural stability to a building.

F2 HAZARDOUS BUILDING MATERIALS – Pryda Connectors and Engineered Systems - Foundation Fixings meet code compliance with NZBC Clause F2.3.1.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10028

Version: 01

Original issue date: 27 March 2024

Version date: 27 March 2024

Product Certificate

Pryda Connectors and Engineered Systems - Foundation Fixings



12. Supporting Information About Conditions and Limitations of Use

All conditions and limitations provided as stated in this Product Certificate.

Signatures

A handwritten signature in black ink that reads "Falck". The signature is written in a cursive style with a large, stylized initial "F".

Claire Falck

CEO, BRANZ Limited.

All CodeMark certificates that are current must be registered with MBIE. MBIE maintains a register of valid product certificates. [Please find the register here.](#)

If the certificate is not listed on this register or it appears as (SUSPENDED), it is not a valid CodeMark certificate and does not have to be accepted by a building consent authority as establishing compliance with the New Zealand Building Code.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.