

MINISTRY OF BUSINESS, INNOVATION & EMPLOYMENT HĪKINA WHAKATUTUKI

Acceptable Solutions and Verification Methods

For New Zealand Building Code Clause F2 Hazardous Building Materials



Status of Verification Methods and Acceptable Solutions

Verification Methods and Acceptable Solutions are prepared by the Ministry of Business, Innovation and Employment in accordance with section 22 of the Building Act 2004. Verification Methods and Acceptable Solutions are for use in establishing compliance with the New Zealand Building Code.

A person who complies with a Verification Method or Acceptable Solution will be treated as having complied with the provisions of the Building Code to which the Verification Method or Acceptable Solution relates. However, using a Verification Method or Acceptable Solution is only one method of complying with the Building Code. There may be alternative ways to comply.

Users should make themselves familiar with the preface to the New Zealand Building Code Handbook, which describes the status of Verification Methods and Acceptable Solutions and explains alternative methods of achieving compliance.

Defined words (italicised in the text) and classified uses are explained in Clauses A1 and A2 of the Building Code and in the Definitions at the start of this document.

Enquiries about the content of this document should be directed to:



MINISTRY OF BUSINESS, INNOVATION & EMPLOYMENT HĪKINA WHAKATUTUKI

Ministry of Business, Innovation and Employment PO Box 1473, Wellingto 6140 Telephone 0800 242 243 Email: info@building.govt.nz

Verification Methods and Acceptable Solutions are available from www.building.govt.nz

New Zealand Government

© Ministry of Business, Innovation and Employment 2016

This document is protected by Crown copyright, unless indicated otherwise. The Ministry of Business, Innovation and Employment administers the copyright in this document. You may use and reproduce this document for your personal use or for the purposes of your business provided you reproduce the document accurately and not in an inappropriate or misleading context. You may not distribute this document to others or reproduce it for sale or profit.

The Ministry of Business, Innovation and Employment owns or has licences to use all images and trademarks in this document. You must not use or reproduce images and trademarks featured in this document for any purpose (except as part of an accurate reproduction of this document) unless you first obtain the written permission of the Ministry of Business, Innovation and Employment.

Document Status

The most recent version of this document (Amendment 3), as detailed in the Document History, is approved by the Chief Executive of the Ministry of Business, Innovation and Employment. It is effective from 1 January 2017 and supersedes all previous versions of this document.

The previous version of this document (Amendment 2) will cease to have effect on 30 May 2017.

People using this document should check for amendments on a regular basis. The Ministry of Business, Innovation and Employment may amend any part of any Verification Method or Acceptable Solution at any time. Up-to-date versions of Verification Methods and Acceptable Solutions are available from www.building.govt.nz

	Date	Alterations	
First published	July 1992		
Amendment 1	19 August 1994	pp. i and ii, Document History p. v, Contents p. vi, References	p. 3, 1.1, 1.1, 1.2, 1.2.1, 1.3 to 1.4.3 deleted p. 4, 1.4.4 deleted p. 5, Index
Reprinted incorporating Amendment 1	July 1996		
Amendment 2	1 December 2000 until 30 May 2017	p. ii, Document History p. vi, References	p. 3, 1.2.1
Amendment 3	Effective 1 January 2017	p. 5 Contents p. 7 References p. 9 Definitions	p. 13 AS1 1.0, 2.0 p. 15 Index

New Zealand Building Code Clause F2 Hazardous Building Materials

This Clause is extracted from the New Zealand Building Code contained in the First Schedule of the Building Regulations 1992.

	00	ulations 1992	1992/150
		ULE—continued	
Clause F2—HAZ	ARDOUS BUILD	ING MATERIALS	
Provis	sions	Limits on a	plication
OBJECTIVE F2.1 The objective provision is to safe from injury and il exposure to <i>hazara</i> materials.	eguard people Iness caused by		
FUNCTIONAL R	EQUIREMENT		
F2.2 <i>Building</i> mate potentially <i>hazardo</i> in ways that avoid people.	erials which are us, shall be used		
PERFORMANCE			
F2.3.1 The quanti liquid, radiation or emitted by materi construction of build give rise to harmf at the surface of t where the materia in the atmosphere	r solid particles als used in the lings, shall not ul concentrations he material l is exposed, or		
F2.3.2 Transparen of being mistaken unimpeded path c marked to make t	for an of travel shall be	Performance F2.3.2 to <i>Housing</i>	2 does not apply
F2.3.3 Glass or ot materials with whi likely to come into	ich people are		
(a) If broken on it way which is u injury, or	mpact, break in a inlikely to cause		
(b) Resist a reasor impact withou			
(c) Be protected f	rom impact.		



Contents

			Page
	Refer	7	
	Defin	9	
	Verifi	11	
	Accep	13	
	1.0	Glazing	13
Amend 3 Jan 2017	1.1	Human impact safety	13
Amend 1 Aug 1994			
	2.0	Asbestos	13
	Index	:	15



References

For the purposes of New Zealand Building Code compliance, the New Zealand and other Standards, and other documents referred to in this Acceptable Solution (primary reference documents) shall be the editions, along with their specific amendments, listed below. Where the primary reference documents refer to other Standards or other documents (secondary reference documents), which in turn may also refer to other Standards or other documents, and so on (lower order reference documents), then the applicable version of these secondary and lower order reference documents shall be the version in effect at the date this Acceptable Solution was published.

Amend 3 Jan 2017

Standards New Zealand

NZS 4223:-

Amends 1 and 2	
Amend 3	

Glazing in buildings Part 3: 2016 Human impact safety requirements Amendment 1

Where quoted

AS1 1.1.1

Jan 2017

Amend 1 Aug 1994

Definitions F2/VM1 & AS1

Definitions

This is an abbreviated list of definitions for words or terms particularly relevant to this Verification Method and Acceptable Solution. The full list of definitions for italicised words may be found in the New Zealand Building Code Handbook.

Asbestos means the asbestiform varieties of				
mineral silicates belonging to the serpentine				
or amphibole groups of rock-forming				
minerals, including the following:				

- (a) actinolite asbestos:
- (b) grunerite (or amosite) asbestos (brown):
- (c) anthophyllite asbestos:
- (d) chrysotile asbestos (white):
- (e) crocidolite asbestos (blue):
- (f) tremolite asbestos:
- (g) a mixture that contains 1 or more of the minerals referred to in paragraphs (a) to (f).
- **Building** has the meaning ascribed to it by Sections 8 and 9 of the Building Act 2004.

Construct in relation to a building, includes to design, build, erect, prefabricate, and relocate the building.

Hazardous Creating an unreasonable risk to people of bodily injury or deterioration of health.

Intended use , in relation to a building,-

(a) includes any or all of the following:

(i) any reasonably foreseeable occasional use that is not incompatible with the *intended use*:

- (ii) normal maintenance:
- (iii) activities undertaken in response to fire or any other reasonably foreseeable emergency; but

Amend 3 Jan 2017

Amend 3 Jan 2017

> (b) does not include any other maintenance and repairs or rebuilding

Safety glass means a glass so treated or combined with other materials as to reduce the likelihood of injury to persons when it is cracked or broken.

Verification Method F2/VM1

Verification Method F2/VM1

No specific test methods have been adopted for verifying compliance with the Performance of NZBC F2.

Acceptable Solution F2/AS1

.....

1.0 Glazing

1.1 Human impact safety

1.1.1 Glazing likely to be subject to human impact shall comply with NZS 4223: Part 3.

COMMENT:

1. NZS 4223: Part 3: 2016 now requires manifestation for shopfronts whereas previously they were exempt.

Transoms or rails with a face width not less than 20 mm and with their centreline between 800 mm and 1200 mm from the finished floor level can provide manifestation.

- 2. F4/AS1 Paragraph 2.1 gives safety from falling requirements for opening windows where the possible fall through the opening is 1 m or more, measured from the adjacent floor level.
- 3. D1/AS1 in Figure 6 shows where open windows could be a dangerous projection..

Amend 2 Dec 2000

Amend 1 Aug 1994

2.0 Asbestos

COMMENT:

New building materials can be expected to be free of asbestos but many *buildings* constructed before the 1990s do include materials that contain asbestos. Therefore, for *alterations* to older *buildings*, Clause F1 'Hazardous Agents on Site' may be relevant because an existing *building* can be considered as part of a site.

The handling of asbestos-containing materials is covered by the Health and Safety at Work (Asbestos) Regulations 2016. These Regulations require the Licensing of asbestos removalists and asbestos assessors.

Refer to the WorkSafe New Zealand website http:// www.business.govt.nz/worksafe/informationguidance/guidance-by-hazard-type/asbestos/workingwith-asbestos

Amend 3 Jan 2017

Amends 1 and 2

Amend 2 Dec 2000

> Amend 3 Jan 2017



Index F2/VM1 & AS1

Index F2/VM1 & AS1

All references to Verification Methods and Acceptable Solutions are preceded by **VM** or **AS** respectively.

Asbestos		AS1 2.0
----------	--	----------------

Glazing

Amend 1 Aug 1994 Amend 3 Jan 2017

human impact	safety	 	AS1 1.1
