Compliance Document for New Zealand Building Code Clause G5 Interior Environment

Prepared by the Department of Building and Housing

This Compliance Document is prepared by the Department of Building and Housing. The Department of Building and Housing is a Government Department established under the State Sector Act 1988.

Enquiries about the content of this document should be directed to:



Department of Building and Housing PO Box 10-729, Wellington. Telephone 0800 242 243 Fax 04 494 0290

Email: info@dbh.govt.nz

Compliance Documents are available from www.dbh.govt.nz

New Zealand Government

© Department of Building and Housing 2011

This Compliance Document is protected by Crown copyright, unless indicated otherwise. The Department of Building and Housing administers the copyright in this document. You may use and reproduce this document for your personal use or for the purposes of your business provided you reproduce the document accurately and not in an inappropriate or misleading context. You may not distribute this document to others or reproduce it for sale or profit.

The Department of Building and Housing owns or has licences to use all images and trademarks in this document. You must not use or reproduce images and trademarks featured in this document for any purpose (except as part of an accurate reproduction of this document) unless you first obtain the written permission of the Department of Building and Housing.

Status of Compliance Documents

Compliance Documents are prepared by the Department of Building and Housing in accordance with section 22 of the Building Act 2004. A Compliance Document is for use in establishing compliance with the New Zealand Building Code.

A person who complies with a Compliance Document will be treated as having complied with the provisions of the Building Code to which the Compliance Document relates. However, a Compliance Document is only one method of complying with the Building Code. There may be alternative ways to comply.

Users should make themselves familiar with the preface to the New Zealand Building Code Handbook, which describes the status of Compliance Documents and explains alternative methods of achieving compliance.

Defined words (italicised in the text) and classified uses are explained in Clauses A1 and A2 of the Building Code and in the Definitions at the start of this Compliance Document.

G5: Document History			
	Date	Alterations	
First published	July 1992		
Amendment 1	1 July 2001	p. 2, Document History, Statusp. 3, NZBCp. 7, Referencesp. 9, Definitions	
Amendment 2	10 October 2011	p. 2, Document History, Status p. 3, Code Clause G5 p. 7, References p. 9, Definitions	

Note: Page numbers relate to the document at the time of Amendment and may not match page numbers in current document.

Document Status

The most recent version of this document, as detailed in the Document History, is approved by the Chief Executive of the Department of Building and Housing. It is effective from 10 October 2011 and supersedes all previous versions of this document.

People using this Compliance Document should check for amendments on a regular basis. The Department of Building and Housing may amend any part of any Compliance Document at any time. Up-to-date versions of Compliance Documents are available from www.dbh.govt.nz

New Zealand Building Code Clause G5 Interior Environment

This Clause is extracted from the New Zealand Building Code contained in the First Schedule of the Building Regulations 1992.

Amend 1 Jul 2001 Amend 2 Oct 2011

FIRST SCHEDULE-continued Clause G5-INTERIOR ENVIRONMENT

Provisions

OBJECTIVE

G5.1 The objective of this provision is to:

- (a) Safeguard people from illness caused by low air temperature,
- (b) Safeguard people from injury or loss of *amenity* caused by inadequate activity space,
- (c) Safeguard people from injury caused by unsafe installations, and
- (d) Ensure that people with disabilities are able to carry out normal activities and processes within buildings.

FUNCTIONAL REQUIREMENT

G5.2.1 *Buildings* shall be *constructed* to provide:

- (a) An *adequate*, controlled interior temperature,
- (b) Adequate activity space for the intended use, and
- (c) Accessible spaces and facilities.

G5.2.2 Heating appliances in *buildings* shall be installed in a way that reduces the likelihood of injury.

PERFORMANCE

G5.3.1 Habitable spaces, bathrooms and recreation rooms shall have the provision for maintaining the internal temperature at no less that 16°C measured at 750 mm above floor level, while the space is adequately ventilated.

Limits on application

Objective G5.1(d) shall apply only to those *buildings* to which section 47A of the Act applies.

Requirement G5.2.1 (a) shall apply only to *habitable spaces*, bathrooms and recreation rooms in old people's homes and early childhood centres.

Requirement G5.2.1 (b) shall apply only to old people's homes. Requirement G5.2.1 (c) shall apply only to Communal Residential, Communal Non-residential, and Commercial buildings.

Performance G5.3.1 shall apply only to old people's homes and early childhood centres.

Note: Section 47A is in the Building Act 1991. The equivalent section in the Building Act 2004 is section 118

Effective from 29 December 2000 INTERIOR ENVIRONMENT Clause G5

FIRST SCHEDULE-continued

Provisions

G5.3.2 Heating appliances, and any attached cables, pipes or other fittings shall be securely fixed in place.

G5.3.3 *Habitable spaces* shall have sufficient space for activity, furniture, and sanitary and mobility aids.

G5.3.4 Where reception counters or desks are provided for public use, at least one counter or desk shall be *accessible*.

G5.3.5 *Buildings* shall be provided with listening systems which enable enhanced hearing by people with hearing aids.

G5.3.6 Enhanced listening systems shall be identified by signs complying the Clause F8 "Signs".

Limits on application

Performance G5.3.2 shall apply only to old people's homes and early childhood centres.

Performance G5.3.3 shall apply only to old people's homes.

Performance G5.3.4 applies only to Communal Residential, Communal Non-Residential, and Commercial buildings.

Performance G5.3.5 applies only to:

- (a) Communal Non-residential assembly spaces occupied by more than 250 people, and
- (b) Any theatre, cinema, or public hall, and
- (c) Assembly spaces in old people's homes occupied by more than 20 people.

Contents

		Page
Refe	rences	7
Defir	nitions	9
Verif	ication Method G5/VM1	11
Acce	ptable Solution G5/AS1	13
1.0	Temperature Control	13
2.0	Space	14
3.0	People with Disabilities	14
Inde	K	15

References

Amend 1 Jul 2001 For the purposes of New Zealand Building Code (NZBC) compliance, the Standards and documents referenced in this Compliance Document (primary reference documents) must be the editions, along with their specific amendments, listed below. Where these primary reference documents refer to other Standards or documents (secondary reference documents), which in turn may also refer to other Standards or documents, and so on (lower-order reference documents), then the version in effect at the date of publication of this Compliance Document must be used.

Amend 2 Oct 2011

			Where quoted
	Standards Assoc	iation of New Zealand	
Amend 1 Jul 2001	NZS 4121: 2001	Design for access and mobility – Buildings and associated facilities	AS1 3.0.1
Amend 2 Oct 2011	NZS 4214: 2006	Methods of determining the total thermal resistance of parts of buildings	Definitions

Definitions

Amend 2

This is an abbreviated list of definitions for words or terms particularly relevant to this Compliance Document. The definitions for any other italicised words may be found in the New Zealand Building Code Handbook.

Accessible Having features to permit use by people with disabilities.

Adequate Adequate to achieve the objectives of the building code.

Amenity An attribute of a building which contributes to the health, physical independence, and well being of the building's users but which is not associated with disease or a specific illness.

Amend 2

Building has the meaning given to it by sections 8 and 9 of the Building Act 2004.

Building element Any structural and nonstructural component or assembly incorporated into or associated with a building. Included are fixtures, services. drains, permanent mechanical installations for access, glazing, partitions, ceilings and temporary supports.

Fixture An article intended to remain permanently attached to and form part of a building.

Habitable space A space used for activities normally associated with domestic living, but excludes any bathroom, laundry, watercloset, pantry, walk-in wardrobe, corridor, hallway, lobby, clothes-drying room, or other space of a specialised nature occupied neither frequently nor for extended periods.

Intended use in relation to a building,—

- (a) includes any or all of the following:
 - (i) any reasonably foreseeable occasional use that is not incompatible with the intended use:
 - (ii) normal maintenance:
 - (iii) activities undertaken in response to fire or any other reasonably foreseeable emergency; but
- (b) does not include any other maintenance and repairs or rebuilding.

Person with a disability means a person who has an impairment or a combination of impairments that limits the extent to which the person can engage in the activities, pursuits, and processes of everyday life, including, without limitation, any of the following:

- (a) a physical, sensory, neurological, or intellectual impairment:
- (b) a mental illness.

R-value The common abbreviation for describing the values of both thermal resistance and total thermal resistance.

Thermal resistance The resistance to heat flow of a given component of a building element. It is equal to the temperature difference (°C) needed to produce unit heat flux (W/m²) through unit area (m²) under steady conditions. The units are °Cm²/W.

Total thermal resistance The overall air-to-air thermal resistance across all components of a building element such as a wall, roof or floor. (This includes the surface resistances which may vary with environmental changes e.g. temperature and humidity, but for most purposes can be regarded as having standard values as given in NZS 4214.)

Amend 1 Jul 2001

Amend 2 Oct 2011

Verification Method G5/VM1

No specific methods have been adopted for verifying compliance with the Performance of NZBC G5.

Acceptable Solution G5/AS1

1.0 Temperature Control

- **1.0.1** Heating to provide acceptable temperature control shall take account of:
- a) Local climate,
- b) Size of the heated space,
- c) Thermal resistance (R-value) of the building elements enclosing the space to be heated, and
- d) Whether the walls of the heated space are internal or external.

- **1.0.2** Indicative *R-values* for different types of *construction* are given in E3/AS1.
- **1.0.3** Tables 1 and 2 provide a method of determining the heating requirements for the *habitable spaces*, bathrooms and recreation rooms of smaller old people's homes and early childhood centres (up to 10 residents), of single storey *construction*. The heating requirements of larger and multi-storey *buildings* shall be specifically calculated.

Table 1:	Paragraph 1.0.3
	Heating wattage (W) for a space whic

		Heating wattage (W) for a space which has			
Locality	Average R-value				
	(the average total thermal resistance of floor, walls and roof/ceiling of the space to be heated)	Four external walls	Three external walls	Two external walls	One external wall
North Island	1.5	720	650	580	510
(see note 2)	0.7	1250	1100	950	800
South Island	1.5	1040	940	840	740
	0.7	1650	1410	1170	930

Notes

- 1. For floor areas exceeding 10 m² use factors given in Table 2.
- 2. North Island localities more than 500 m above sea level shall meet South Island requirements.

Table 2:	Multiplying Factors for Determining Acceptable Wattage in Spaces Exceeding 10 m ² Floor Area
	Paragraph 1.0.3 and Table 1

Floor area (m²)	10	20	40	80	160
Multiplying factor	1.0	1.4	2.0	2.8	4.0

Note:

Interpolation for different floor areas is permitted.

1.0.4 Example of use of Tables 1 and 2:

For a space (South Island) of 20 m² and an average *R-value* of 1.5, with 2 external walls, the necessary heating power is:

840 (Table 1) \times 1.4 (Table 2) = 1176 W

The average R-value for example may be

$$\frac{0.4 \text{ (floor)} + 2.0 \text{ (walls)} + 3.0 \text{ (roof)}}{3} = \frac{5.4}{3} = 1.8$$

In this case the wattage is read from the 1.5 Average *R-value* line, in Table 1.

2.0 Space

- **2.0.1** Each old people's home shall have spaces for living, dining and sleeping.
- **2.0.2** Spaces for living and dining may be combined provided that the total space can, if necessary, be divided into separate living and dining areas each satisfying their respective requirements for width and floor area.
- **2.0.3** Spaces provided shall have dimensions of no less than those given in Table 3.

3.0 People with Disabilities

3.0.1 Acceptable activity space shall comply with NZS 4121.

Table 3:	Space Provision for Old Paragraph 2.0.3	l People's Ho	mes
			Minimum dimensions
Type of spa	ce	Width (m)	Floor area (m²)
Living room		2.75	10 + 1 for each resident over 3 in number
Dining room		2.75	8 + 1 for each resident over 3 in number
Bedroom		2.2	6 for each resident (see note 1)

Note:

 Floor area for bedrooms shall exclude built-in wardrobes. In the absence of a built-in wardrobe, an additional 0.75 m² shall be provided for each resident. Index G5/VM1 & AS1 INTERIOR ENVIRONMENT

Index G5/VM1 & AS1

All references to Verification Methods and Acceptable Solutions are preceded by **VM** or **AS** respectively.

Early childhood centres	AS1 1.0.3
Old people's homes	AS1 1.0.3, 2.0, Table 3
People with disabilities	AS1 3.0
Space requirements	AS1 2.0, Table 3
Temperature control	AS1 1.0 Tables 1 and 2