

MINISTRY OF BUSINESS, INNOVATION & EMPLOYMENT HĪKINA WHAKATUTUKI



Effective until 3 November 2021 Replaced by G9 First Edition Amendment 7

## Acceptable Solutions and Verification Methods

# For New Zealand Building Code Clause **G9 Electricity**

**G9** BUILDING CODE

# ARCHIVED

### **Status of Verification Methods and Acceptable Solutions**

Verification Methods and Acceptable Solutions are prepared by the Ministry of Business, Innovation and Employment in accordance with section 22 of the Building Act 2004. Verification Methods and Acceptable Solutions are for use in establishing compliance with the New Zealand Building Code.

A person who complies with a Verification Method or Acceptable Solution will be treated as having complied with the provisions of the Building Code to which the Verification Method or Acceptable Solution relates. However, using a Verification Method or Acceptable Solution is only one method of complying with the Building Code. There may be alternative ways to comply.

Users should make themselves familiar with the preface to the New Zealand Building Code Handbook, which describes the status of Verification Methods and Acceptable Solutions and explains alternative methods of achieving compliance.

Defined words (italicised in the text) and classified uses are explained in Clauses A1 and A2 of the Building Code and in the Definitions at the start of this document.

Enquiries about the content of this document should be directed to:



MINISTRY OF BUSINESS, INNOVATION & EMPLOYMENT HĪKINA WHAKATUTUKI

Ministry of Business, Innovation and Employment PO Box 1473, Wellington. Telephone 0800 242 243 Fax 04 494 0290 Email: info@dbh.govt.nz

Verification Methods and Acceptable Solutions are available from www.dbh.govt.nz

### New Zealand Government

© Ministry of Business, Innovation and Employment 2014

This document is protected by Crown copyright, unless indicated otherwise. The Ministry of Business, Innovation and Employment administers the copyright in this document. You may use and reproduce this document for your personal use or for the purposes of your business provided you reproduce the document accurately and not in an inappropriate or misleading context. You may not distribute this document to others or reproduce it for sale or profit.

The Ministry of Business, Innovation and Employment owns or has licences to use all images and trademarks in this document. You must not use or reproduce images and trademarks featured in this document for any purpose (except as part of an accurate reproduction of this document) unless you first obtain the written permission of the Ministry of Business, Innovation and Employment.

# ARCHIVED

### **Document Status**

The most recent version of this document (Amendment 6), as detailed in the Document History, is approved by the Chief Executive of the Ministry of Business, Innovation and Employment. It is effective from 14 February 2014 and supersedes all previous versions of this document.

The previous version of this document (Amendment 5) will cease to have effect on 14 August 2014.

People using this document should check for amendments on a regular basis. The Ministry of Business, Innovation and Employment may amend any part of any Verification Method or Acceptable Solution at any time. Up-to-date versions of Verification Methods and Acceptable Solutions are available from www.dbh.govt.nz

	Date	Alterations	
First published	July 1992		
Amendment 1	September 1993	p. vi, References p. 1, 1.0.1	p. 3, 1.0.1 p. 4, Index
Amendment 2	1 December 1995	pp. i and ii, Document History p. vi, References	p. 1, 1.0.1
Amendment 3	1 July 2001	p. 2, Document History, Status p. 9, Definitions	
Amendment 4	23 June 2007	p. 2, Document History, Status p. 7, References p. 9, Definitions	p. 11 VM1 p. 13 AS1, 1.0.1, 2.0.1
Amendment 5	Published 30 June 2010 Effective from 30 September 2010 until 14 August 2014	p. 2, Document History, Status p. 3, Code Clause G9 p. 7, References	
Reprinted incorporating Amendments 1–5	30 September 2010		
Amendment 6	14 February 2014	p. 2A, Document History, Status p. 7, References	p. 9, Definitions



## New Zealand Building Code Clause G9 Electricity **ARCHIVED**

This Clause is extracted from the New Zealand Building Code contained in the First Schedule of the Building Regulations 1992.

FIRST SCHEDULE—continued		
Clause G9–ELECTRICITY		
Provisions	Limits on application	
<ul> <li>OBJECTIVE</li> <li>G9.1 The objective of this provision is to ensure that:</li> <li>(a) In <i>buildings</i> supplied with electricity, the <i>electrical installation</i> has safeguards against outbreak of <i>fire</i> and personal injury, and</li> </ul>		
(b) <i>People with disabilities</i> are able to carry out normal activities and processes within <i>buildings</i> .	Objective G9.1(b) shall apply only to those <i>buildings</i> to which section 47A of the Act applies.	Ar Se
<b>FUNCTIONAL REQUIREMENT</b> <b>G9.2</b> Where provided in a <i>building, electrical installations</i> shall be safe for their <i>intended use</i> .		
<b>PERFORMANCE</b> <b>G9.3.1</b> The <i>electrical installation</i> shall incorporate systems to:		
<ul> <li>(a) protect people from contact with parts of the installation which are live during normal operation, and to prevent parts of the installation or other <i>building elements</i> becoming live during fault conditions,</li> </ul>		
<ul> <li>(b) permit the safe isolation of the installation and of electrical fittings and appliances,</li> </ul>		
<ul> <li>(c) safeguard people from excessive temperatures resulting from either normal operation of electrical equipment, or from currents which could exceed the installation rating,</li> </ul>		
<ul> <li>(d) safeguard people from injury which may result from electromechanical stress in electrical components caused by currents in excess of the installation rating,</li> </ul>		

-----

### NOTE:

Section 47A is in the Building Act 1991. The equivalent section in the Building Act 2004 is section 118.

# <u>ARCHIVED</u>

Image: Provision of their physical or mechanical properties, or function, due to granter increases resulting properties, or function, due to granter increases resulting to their physical or mechanical environment, and       Limits on application         (9) Operate safely in its intended environment, and       8.       Safeguard against ignition of the surrounding atmosphere where it is potentially fummable or explosive.       9.31 An electrical installation supply for a time appropriate to that service, shall.       9. Be capable of being isolated finance of the installation.         (9) Be capable of being isolated finander of the installation.       9.33 An electrical installation properties to that service, shall on the supply system, shall contain safeguards.       Performance G9.3.4 shall not granter in the supply for a time supply of the installation.         (9) Safe under the installation for the installation.       Performance G9.3.4 shall not application.         (9) Safe under the installation supply in the supply of the installation.       Performance G9.3.4 shall not industrial supply in the installation.         (9) Safe under the installation for the installation for the external supply.       Performance G9.3.4 shall not industrial supply in the installation.         (9) Safe under the installation for the external supply.       Performance G9.3.4 shall not industrial supply to Housing, Outbuildings, and to Industrial supply to Housing. Outbuildings, and to Industrial supply in the installation.	Provisions       Limits on application         (e) Protect building elements from risk of ignition, impairment of their physical or mechanical properties, or function, due to temperature increases resulting from heat transfer or electric arc,       Limits on application         (f) Operate safely in its intended environment, and       (g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.       (g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.       (g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.         G9.3.2 An electrical installation supplying an essential service, and       (h) Be capable of being isolated from the supply system, independently of the remainder of the installation.         G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.       Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10	1992/150	Building Re	gulations 1992 3	87
<ul> <li>(e) Protect building elements from risk of ignition, impairment of their physical or mechanical properties, or function, due to temperature increases resulting from heat transfer or electric arc,</li> <li>(f) Operate safely in its intended environment, and</li> <li>(g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.</li> <li><b>G9.3.2</b> An electrical installation supplying an essential service shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> </ul>	<ul> <li>(e) Protect building elements from risk of ignition, impairment of their physical or mechanical properties, or function, due to temperature increases resulting from heat transfer or electric arc,</li> <li>(f) Operate safely in its intended environment, and</li> <li>(g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.</li> <li><b>G9.3.2</b> An electrical installation supplying an essential service shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> </ul>	FIRST SCHEDULE—continued			
<ul> <li>risk of ignition, impairment of their physical or mechanical properties, or function, due to temperature increases resulting from heat transfer or electric arc,</li> <li>(f) Operate safely in its intended environment, and</li> <li>(g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.</li> <li><b>G9.3.2</b> An <i>electrical installation</i> supplying an <i>essential service</i> shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An <i>electrical installation</i> connected to an <i>electrical supply</i> system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In <i>buildings</i> intended for use by <i>people with disabilities</i>, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, <i>Outbuildings</i>, <i>Ancillary Buildings</i>, and to <i>Industrial Buildings</i> where no more than 10</li> </ul>	<ul> <li>risk of ignition, impairment of their physical or mechanical properties, or function, due to temperature increases resulting from heat transfer or electric arc,</li> <li>(f) Operate safely in its intended environment, and</li> <li>(g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.</li> <li><b>G9.3.2</b> An <i>electrical installation</i> supplying an <i>essential service</i> shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An <i>electrical installation</i> connected to an <i>electrical supply</i> system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In <i>buildings</i> intended for use by <i>people with disabilities</i>, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not anyly to Housing, <i>Outbuildings</i>, <i>Ancillary Buildings</i>, and to <i>Industrial Buildings</i> where no more than 10</li> </ul>	Pro	ovisions	Limits on application	
<ul> <li>environment, and</li> <li>(g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.</li> <li><b>G9.3.2</b> An <i>electrical installation</i> supplying an <i>essential service</i> shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An <i>electrical installation</i> connected to an <i>electrical supply</i> system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In <i>buildings</i> intended for use by <i>people with disabilities</i>, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, <i>Outbuildings</i>, <i>Ancillary Buildings</i>, and to <i>Industrial</i> <i>Buildings</i> where no more than 10</li> </ul>	<ul> <li>environment, and</li> <li>(g) Safeguard against ignition of the surrounding atmosphere where it is potentially flammable or explosive.</li> <li><b>G9.3.2</b> An <i>electrical installation</i> supplying an <i>essential service</i> shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An <i>electrical installation</i> connected to an <i>electrical supply</i> system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In <i>buildings</i> intended for use by <i>people with disabilities</i>, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, <i>Outbuildings</i>, <i>Ancillary Buildings</i>, and to <i>Industrial</i> <i>Buildings</i> where no more than 10</li> </ul>	risk of ignit their physic properties, temperatur from heat t	ion, impairment of eal or mechanical or function, due to e increases resulting		
<ul> <li>the surrounding atmosphere where it is potentially flammable or explosive.</li> <li>G9.3.2 An electrical installation supplying an essential service shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li>G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li>G9.3.4 In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings where no more than 10</li> </ul>	<ul> <li>the surrounding atmosphere where it is potentially flammable or explosive.</li> <li>G9.3.2 An electrical installation supplying an essential service shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li>G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li>G9.3.4 In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings where no more than 10</li> </ul>				
<ul> <li>supplying an essential service shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10</li> </ul>	<ul> <li>supplying an essential service shall:</li> <li>(a) Maintain the supply for a time appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li><b>G9.3.3</b> An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li><b>G9.3.4</b> In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, and to Industrial Buildings where no more than 10</li> </ul>	the surrour where it is	iding atmosphere potentially		
<ul> <li>appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li>G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li>G9.3.4 In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10</li> </ul>	<ul> <li>appropriate to that service, and</li> <li>(b) Be capable of being isolated from the supply system, independently of the remainder of the installation.</li> <li>G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li>G9.3.4 In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10</li> </ul>				
<ul> <li>from the supply system, independently of the remainder of the installation.</li> <li>G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li>G9.3.4 In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10</li> </ul>	<ul> <li>from the supply system, independently of the remainder of the installation.</li> <li>G9.3.3 An electrical installation connected to an electrical supply system, shall contain safeguards which protect the safety features of the external supply.</li> <li>G9.3.4 In buildings intended for use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.</li> <li>Performance G9.3.4 shall not apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10</li> </ul>				
<ul> <li>connected to an <i>electrical supply</i></li> <li>system, shall contain safeguards</li> <li>which protect the safety features</li> <li>of the external supply.</li> <li><b>G9.3.4</b> In <i>buildings</i> intended for</li> <li>use by <i>people with disabilities</i>, light</li> <li>switches and plug socket outlets</li> <li>shall be accessible and usable.</li> <li>Performance G9.3.4 shall not</li> <li>apply to Housing, <i>Outbuildings</i>,</li> <li>Ancillary Buildings, and to Industrial</li> <li>Buildings where no more than 10</li> </ul>	<ul> <li>connected to an <i>electrical supply</i></li> <li>system, shall contain safeguards</li> <li>which protect the safety features</li> <li>of the external supply.</li> <li>G9.3.4 In <i>buildings</i> intended for</li> <li>use by <i>people with disabilities</i>, light</li> <li>switches and plug socket outlets</li> <li>shall be accessible and usable.</li> <li>Performance G9.3.4 shall not</li> <li>apply to Housing, <i>Outbuildings</i>,</li> <li>Ancillary Buildings, and to Industrial</li> <li>Buildings where no more than 10</li> </ul>	from the su independen	pply system, tly of the		
use by <i>people with disabilities</i> , light switches and plug socket outlets shall be <i>accessible</i> and usable. apply to Housing, <i>Outbuildings</i> , <i>Ancillary Buildings</i> , and to <i>Industrial</i> <i>Buildings</i> where no more than 10	use by people with disabilities, light switches and plug socket outlets shall be accessible and usable.apply to Housing, Outbuildings, Ancillary Buildings, and to Industrial Buildings where no more than 10	connected to ar system, shall co which protect t	n <i>electrical supply</i> ontain safeguards he safety features		
		use by <i>people w</i> switches and pl	<i>ith disabilities</i> , light ug socket outlets	apply to Housing, Outbuildings, Ancillary Buildings, and to Industria Buildings where no more than 10	al

4

-----

Contents G9/VM1 & AS1

## Contents

		Page
Refer	rences	7
Defin	itions	9
Verifi	ication Method G9/VM1	11
1.0	Electrical Installations	11
Acce	ptable Solution G9/AS1	13
1.0	Electrical Installations Within Domestic Dwellings	13
2.0	Light Switches and Plug Sockets for use by People with Disabilities	13
Index	κ.	15





References G9/VM1 & AS1

## References

Where guoted

For the purposes of New Zealand Building Code compliance, the acceptable New Zealand and other Standards, and other documents referred to in this Verification Method and Acceptable Solution (primary reference documents) shall be the editions, along with their specific amendments, listed below. Where the primary reference documents refer to other Standards or other documents (secondary reference documents), which in turn may also refer to other Standards or other documents, and so on (lower order reference documents), then the applicable version of these secondary and lower order reference documents shall be the version in effect at the date this Verification Method and Acceptable Solution were published.

Amend 4 Jun 2007

	Standards New Z	Zealand	-
A	AS/NZS 3000: 200	7 Electrical installations	VM1 1.0.1,
Amends 5 and 6		Amends: 1 and 2	AS1 2.0.1
	Publications by N	lew Zealand Ministry of Economic Development	
	NZECP 34: 2001	Electrical safety distances	VM1 1.0.1
	NZECP 36: 1993	Harmonic levels	VM1 1.0.1
	NZECP 51: 2004	Homeowner/occupier's electrical wiring work in domestic installations	AS1 1.0.1
Amend 4 Jun 2007	NZECP 54: 2001	Installation of recessed luminaires and auxiliary equipment	VM1 1.0.1

Amend 6 Feb 2014

Amend 6 Feb 2014



Definitions G9/VM1 & AS1

Amend 4

Jun 2007

# Definitions

# ARCHIVED

This is an abbreviated list of definitions for words or terms particularly relevant to this Verification Method and Acceptable Solution. The definitions for any other italicised words may be found in the New Zealand Building Code Handbook.

Amend 6 Feb 2014

Accessible Having features to permit use by

- a *person with a disability.* Building has the meaning ascribed to
- **Building** has the meaning ascribed to it by Sections 8 and 9 of the Building Act 2004.
- **Building element** Any structural and nonstructural component or assembly incorporated into or associated with a *building*. Included are *fixtures*, services, *drains*, permanent mechanical installations for access, glazing, partitions, ceilings and temporary supports.
- **Electrical installation** Any electrical fixed appliances, and components used in the reticulation of electricity, which are intended to remain permanently attached to and form part of the *building*.
- **Electrical supply system** The source of electricity external to the *electrical installation*.
- **Essential service** In the context of an *electrical installation* means emergency lighting, firemen's lifts, alarms, water pumps, sprinklers, detectors, ventilation systems and public address systems necessary for the safety of people in *buildings*.

Intended use in relation to a *building*:

- a) includes any or all of the following:
  - Any reasonably foreseeable occasional other use that is not incompatible with the *intended use*; and
  - ii) Normal maintenance; and
  - iii) Activities taken in response to *fire* or any other reasonably foreseeable emergency

Amend 4 Jun 2007  b) but does not include any other maintenance and repairs or rebuilding.

## Person with a disability means a person

who has an impairment, or a combination of impairments, that limits the extent to which the person can engage in the activities, pursuits and processes of everyday life, including, without limitation, any of the following:

- a) a physical, sensory, neurological, intellectual impairment or
- b) a mental illness.

Amend 4 Jun 2007



# Verification Method G9/VM1 **ARCHIVED**

### **1.0 Electrical Installations**

1.0.1 The following documents shall be accepted as a method of verifying compliance with the relevant Performances of NZBC G9:

AS/NZS 3000, NZECP 34, NZECP 36, and Amend 4 Jun 2007 NZECP 54.

-----



## Acceptable Solution G9/AS1 **ARCHIVED**

## 1.0 Electrical Installations within **Domestic Dwellings**

Amend 4 Jun 2007

Amend 1

Sep 1993

1.0.1 NZECP 51 is an Acceptable Solution for electrical installations within domestic dwellings.

## 2.0 Light Switches and Plug Sockets for use by a Person with a Disability

Amend 4 Jun 2007 2.0.1 In *buildings* intended for use by *persons* with disabilities, light switches and socket outlets shall comply with the following requirements:

- a) All light switches shall be horizontally aligned with door handles.
- b) The toggle, rocker, push pad, or push button control of light switches shall project clear of the switch plate.

### COMMENT:

It is recommended that the width of any push pad or button be no less than 20 mm.

c) Socket outlets in accessible accommodation units shall be fixed between 500 mm and 1200 mm above the finished floor level and at least 500 mm from corners. At least one room light shall have a bedside switch.

Paragraph 2.0.1 shall not apply in damp situations where the location of the light switch and plug sockets conflicts with AS/NZS 3000.

Amend 4 Jun 2007

DEPARTMENT OF BUILDING AND HOUSING





Index G9/VM1 & AS1

# Index G9/VM1 & AS1

All references to Verification Methods and Acceptable Solutions are preceded by VM or AS respectively.

	Domestic buildings	
Amend 1 Sep 1993	Electrical codes of practice	<b>VM1</b> 1.0.1, <b>AS1</b> 1.0.1
Amend 1	Electrical installations	<b>VM1</b> 1.0
Sep 1993	Light switches	<b>AS1</b> 2.0.1 a) b)
	People with disabilities	
	Socket outlets	<b>AS1</b> 2.0.1 c)

